



SEC "UL" Series of Battery Chargers

The all NEW SEC UL Series Battery Chargers are fully automatic and based on Samlex's industry proven SEC design that professionals have depended on for years. Packed with added features and certified to meet stringent UL Safety Standards, the SEC UL Series provides reliable charging and trouble free battery maintenance...



PRODUCT FEATURES

- High efficiency
- Commercial Grade
- Lightweight
- Quiet operation
- Industry Proven Design – 1000s of units in operation
- 2 or 3 stage charging (user selectable)
- 120 or 230 VAC, 50/60 Hz (user selectable)
- Voltage meter display
- For all types of Lead Acid batteries
- Charge with a battery load – or stand alone
- Use as a power supply or DC UPS
- UPC: Universal Protection Circuit – short circuit, overload, reverse battery polarity
- Charge 3 banks of batteries at once – no isolator necessary (SEC-1215UL, SEC-1230UL, SEC-2415UL)
- "Half Power Mode" – reduces maximum charging current to half the rated capacity, allows for safe charging of lower capacity batteries (SEC-1250UL, SEC-1280UL, SEC-2425UL, SEC-2440UL)
- Temperature Compensated Charging Circuit – to prevent under/overcharging of battery if temperature varies extensively (SEC-1250UL, SEC-1280UL, SEC-2425UL, SEC-2440UL)
- Safety certified – meets UL Standard UL-1564, EMI Compliant to FCC Part 15 (B), Class B

MODEL	INPUT	OUTPUT	CHARGING CURRENT
SEC-1215UL	120 VAC	12 VDC	15A
SEC-1230UL	120 VAC	12 VDC	30A
SEC-2415UL	120 VAC	24 VDC	15A
SEC-1250UL	120 VAC	12 VDC	50A
SEC-2425UL	120 VAC	24 VDC	25A
SEC-1280UL	120 VAC	12 VDC	80A
SEC-2440UL	120 VAC	24 VDC	40A
900-RC	For use with SEC-1250, 1280, 2425, 2440.		

2 YEAR WARRANTY

Accessories

900-RC Remote Control

- Comes with 33' cable. The Remote Panel can be used to power ON/OFF and also monitor the charging status from a remote location.
- Half Power Mode allows smaller capacity batteries to be charged safely at a lower current.
- For use with SEC-1250, 1280, 2425, 2440.



ORDER NOW

sales@samlexamerica.com

1 800 561 5885

www.samlexamerica.com

For complete product information (weights and dimensions), images and roll out schedule email: marketing@samlexamerica.com