



samlexamerica®

900-RC



**Battery
Charger
Remote
Control**

Model
900-RC

Design Features

- Compatible with the following series of Battery Chargers:
 - SEC-1250UL, SEC-1280UL
 - SEC-2425UL, SEC-2440UL
- Displays operational status and charging stages using colored LEDs
- Includes 10M / 33' of RJ-45 (8P8C) cable set

Wired Remote Control to switch ON/OFF and monitor battery charger from remote location.

2 YEAR LIMITED WARRANTY

	MODEL NO.	900-RC
DISPLAY	GREEN LED	Marked "POWER" – Indicates ON condition
	GREEN LED	Marked "FLOAT" – Indicates Float Stage
	YELLOW LED	Marked "ABSORPTION" – Indicates Boost / Absorption Stage
	RED LED	Marked "BULK" – Indicates Bulk Stage
CONNECTIONS	INPUT CONNECTOR	RJ-45 Modular Jack (8P8C)
	CONNECTING CABLE SET	8 Conductors, RJ-45 (8P8C) plugs; Straight; Length: 10M / 33'
GENERAL	OPERATING TEMPERATURE	0°C – 40°C / 32°F – 104°F
	DIMENSIONS (W x D x H), INCHES	2.54 x 1.0 x 4.28
	DIMENSIONS (W x D x H), MM	64.5 x 25.4 x 108.7
	WEIGHT, LB	0.80
	WEIGHT, KG	0.36

NOTE: Specifications are subject to change without notice